



cantech.com

205-**

CONTRACTORS' SHEATHING TAPE



DESCRIPTION

This tape is made of a UV resistant polypropylene film and coated with high shear, high tack solvent based acrylic adhesive.

** This tape is meant for permanent application only.
It will leave adhesive residue if removed.*

MAIN FEATURES

- High tack adhesive provides aggressive contact.
- Strong and durable holding power.
- Water and moisture resistant.
- Excellent resistance to UV and weathering.
- Prevents air infiltration.
- CCMC Evaluation Report #11955-R.

APPLICATIONS

- Sealing of joints and seams of insulation materials.
- Tape has to be pressed firmly on surface.
- Should be applied on clean, dry surfaces.

TECHNICAL DATA

Colour	Red (02), White (10)
Backing	UV Resistant Polypropylene Film
Adhesive.....	Solvent Based Acrylic
Thickness.....	3 mil
Adhesion to steel.....	40 oz/in
Tensile strength.....	30 lb/in
Elongation.....	120%
Application Temperature.....	-18°C (0°F) to 50°C (122°F)
Temperature Resistance	-40°C (-40°F) to 100°C (212°F)
VOC (Volatile Organic Compound) content	Estimated 0,1%
Moisture Vapor Transmission Rate.....	3.9x10 ⁻⁹ g/Pa s m ² (Test in accordance with ASTM E 96-00e1)
Water Penetration Rate.....	0.009 g/100 in ² (Test in accordance with ASTM D 3816 / D 3816M-96)
Air Permeance Rate	0.0010 L/s m ² (Test in accordance with ASTM E2178-13)

STOCK SIZE

60mm x 66m — 20 rolls/case

Please note:

Values quoted are averages only and may vary within industry tolerances. The final user must assure product suitability for the application and assumes all risks and liabilities.



STRONG HOLDING POWER

HIGH TACK ADHESIVE